


| | | | | | |
|--------------|--------------------------|---|-----------------------------|--------------------------|---------------------------|
| Features | Dimension L * W * H (mm) | 32.5 * 27.5 * 20 | | | |
| | Terminal Type | PCB | | | |
| | Weight | 30 gm Approximately | | | |
| Contact Data | Contact Form | 1A, 1C | | | |
| | Contact Material | Ag Alloy | | | |
| | Contact Capacity | 30A @ 250VAC, 30A @ 28VDC | | | |
| Coil Data | Coil Voltage (DC) | 5 ~ 24 VDC | | | |
| | Coil Power Consumption | 0.93W | | | |
| | Coil Specification | Coil Voltage | Coil Resistance (Ω) ±10% | Pull in Voltage (VDC) | Drop Out Voltage (VDC) |
| | | 12 VDC | 155 | 80% | 5% |
| | | 24 VDC | 660 | 80% | 5% |
| General Data | Dielectric Strength | 1500 VAC @ 50 Hz / Min (Between Open Contacts) 2500 VAC @ 50 Hz / Min (Between Coil & Contacts) | | | |
| | Insulation Resistance | 500MΩ | | | |
| | Electrical Life | 1 x 10 ⁵ | | | |
| | Mechanical Life | 1 x 10 ⁷ | | | |
| | Operating Temperature | - 55°C ~ + 85°C | | | |

Mounting Diagram



Application

HVAC, Domestic application, Car Control Switching Box etc.